

IP Camera

**VIA-IPC-4DP-LIVA2M**

**VIA-IPC-4DP-LIVA2M** is a 4 MP network camera featuring a motorized varifocal lens designed for easy installation and precise monitoring.

The device integrates a 1/3» Progressive Scan CMOS sensor and Fusion Illumination technology, which combines IR and White lights to provide adaptable supplemental lighting.

It utilizes SMART-TC deep learning algorithms for focused human and vehicle classification, alongside a built-in arrayed dual-microphone for real-time, high-quality audio security.

The camera metal housing rated IP67 for weather resistance and IK10 for vandal resistance.

**Key Capabilities**

- ✓ 4 MP resolution (2688 × 1520)
- ✓ Motorized varifocal lens, 2.8 to 12 mm
- ✓ Fusion Illumination system (IR + white light), up to 40 m
- ✓ 120 dB WDR
- ✓ H.265 / H.264 video compression
- ✓ SMART-TC (Smart Target Classification) - Human and vehicle classification
- ✓ Face detection
- ✓ Built-in arrayed dual-microphone
- ✓ IP67 weather protection, IK10 vandal resistance
- ✓ Support for microSD up to 512 GB

VIA Security

 **UKRAINIAN  
BRAND****Fusion  
ILLUMINATION**

# SPECIFICATION

## CAMERA

**Image Sensor**

1/3" Progressive Scan CMOS

**Max. Resolution**

2688 × 1520

**Min. Illumination**

Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with light

**Shutter Time**

1/3 s to 1/100,000 s

**Day & Night**

IR cut filter

**Angle Adjustment**

Pan: 0° to 355°, tilt: 0° to 75°, rotate: 0° to 355°

## OPTICAL SYSTEM

**Lens Type**

Varifocal lens, motorized lens, 2.8 to 12 mm

**Focal Length & FOV**

2.8 to 12 mm, horizontal FOV 102.4° to 31.2°, vertical FOV 54.7° to 17.6°, diagonal FOV 122.1° to 35.8°

**Focus**

Ø 14

**Iris Type**

Fixed

**Aperture**

F1.6

## ILLUMINATION

**Supplement Light Range**

Up to 40 m

**Supplement Light Type**

IR, White Light

**Smart Supplement Light**

Yes

**IR Wavelength**

850 nm

## VIDEO PROCESSING & ENCODING

**Main Stream**

50 Hz: 25 fps (2688 × 1520, 1920 × 1080, 1280 × 720); 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)

**Sub-Stream**

50 Hz: 25 fps (1280 × 720, 640 × 480, 640 × 360); 60 Hz: 30 fps (1280 × 720, 640 × 480, 640 × 360)

**Third Stream**

50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360); 60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360), \*Third stream is supported under certain settings.

**Video Compression**

Main stream: H.265/H.264, Sub-stream: H.265/H.264/MJPEG, Third stream: H.265/H.264, \*Third stream is supported under certain settings.

**Video Bit Rate**

32 Kbps to 8 Mbps

**H.264 Type**

Baseline Profile, Main Profile, High Profile

**H.265 Type**

Main Profile

**Bit Rate Control**

CBR, VBR

**Scalable Video Coding (SVC)**

H.264 and H.265 encoding

**Region of Interest (ROI)**

1 fixed region for main stream and sub-stream

**Target Cropping**

Yes

## AUDIO CAPABILITIES

**Audio Compression**

G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC

**Audio Bit Rate**

64 Kbps (G.711ulaw/G.711alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)

**Audio Sampling Rate**

8 kHz/16 kHz/32 kHz/48 kHz

**Environment Noise Filtering**

Yes

## NETWORK & CYBERSECURITY

**Protocols**

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets

**Simultaneous Live View**

Up to 6 channels

**API**

ONVIF (Profile S, Profile G), SDK

**Security**

Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface

**User/Host**

Up to 32 users, 3 user levels: administrator, operator, and user

**Network Storage**

NAS (NFS, SMB/CIFS), Auto Network Replenishment (ANR).

**Web Browser**

Plug-in required live view: IE 11; Plug-in free live view: Chrome 80+, Firefox 80+, Edge 89+, Safari 13+; Local service: Chrome 80+, Firefox 80+, Edge 89+, Safari 13+

## IMAGE

**Image Parameters Switch**

Yes

**Image Settings**

Rotate mode

**Day/Night Switch**

Day, Night, Auto, Schedule

**Wide Dynamic Range (WDR)**

120 dB

**SNR**

≥ 52 dB

**Image Enhancement**

BLC, HLC, 3D DNR

**Privacy Mask**

8 programmable polygon privacy masks

## INTERFACE

**Ethernet Interface**

1 RJ45 10 M/100 M self-adaptive Ethernet port

**On-Board Storage**

Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

**Audio**

Built-in Microphone: Arrayed dual-microphone, 1 input (line in), two-core terminal block, 1 output (line out), two-core terminal block

**Alarm**

1 input, 1 output (max. 24 VDC/24 VAC, 1 A)

**Reset Key**

Yes

## EVENT

**Basic Event**

Motion detection (support alarm triggering by specified target types (human and vehicle)), video tampering alarm, exception

**Smart Event**

Face detection

**Linkage**

Upload to FTP/NAS/memory card, notify surveillance center, send email, trigger alarm output, trigger recording, trigger capture

## DEEP LEARNING FUNCTION

**Perimeter Protection**

Line crossing, intrusion, Support alarm triggering by specified target types (human and vehicle)

## GENERAL

**Power**

12 VDC ± 25%, 0.88 A, max. 10.56 W, Ø 5.5 mm coaxial power plug, reverse polarity protection; PoE: IEEE 802.3af, Class 3, max. 12.5 W

**Material**

Metal

**Dimension**

Ø 121.5 mm × 97.6 mm (Ø 4.78" × 3.84")

**Package Dimension**

150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.5")

**Weight**

Approx. 620 g (1.4 lb.)

**With Package Weight**

Approx. 880 g (1.9 lb.)

**Storage Conditions**

30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)

**Startup and Operating Conditions**

-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)

**Language**

Multi-language interface including English, Ukrainian, Russian and additional international languages.

**General Function**



Heartbeat, mirror, flash log, password reset via email, pixel counter, anti-banding

**Protection**

IP67, IK10



## DIMENSIONS



Unit: mm (inch)

\*Product in box may vary in appearance and specifications.



Limited liability company «VIATEK»

Email: [info@viasecurity.ua](mailto:info@viasecurity.ua)  
For more detailed information: [viasecurity.ua](http://viasecurity.ua)

**UKRAINIAN  
BRAND**